



GA/45R

### **Caratteristiche Tecniche**

- Struttura in acciaio con profilati scatolati ad angoli arrotondati e vetri blindati omologati antivandalismo (UNI 9186) ed antiproiettile-antischeggia classe A (UNI 9187) dello spessore di 19 mm.
- I catenacci di chiusura sono azionati da una maniglia e da un meccanismo centralizzato a triplice espansione, bloccato da una serratura con cilindro di sicurezza a profilo europeo.
- Sportello con apertura a 180°, cerniere interne e profilo antistrappo.
- Allestimento interno con 3 ripiani in cristallo spostabili su cremagliera.
- Illuminazione interna con due faretto posti nella parte interna superiore.
- Vetri blindati sui 3 lati e pannello interno di fondo rivestito in tessuto di colore blu.
- Fori di ancoraggio sulla base.
- Verniciatura a polvere termoindurente con essiccazione a forno in RAL 9006 (alluminio satinato).

**GA/45R:** • 3 ripiani

**GA/70R:** • 3 ripiani

### **Technical Characteristics**

- One-piece steel construction built with box vertical posts and strong 19mm thick security glass that conforms to UNI 9186 (for light mechanical attacks) and UNI 9187 class A (against bullets).
- Locking bolts are operated by a handle that drives a 3-way expanding mechanism, and are secured by a high security drill resistant cylinder lock.
- Doors open to 180°, and are hung on non visible hinges.
- Supplied with 3 crystal glass shelves that can be placed on the rack.
- 2 internal spot lights built-in to the top cover.
- 3 sides made from strong 19mm thick security glass and internal back-side covered with a elegant cloth in the colour blue.
- Fixing holes on the base.
- Oven dried thermo-hardening powder painting in colours RAL 9006 (light steel grey).

**GA/45R:** • 3 shelves

**GA/70R:** • 3 shelves



Art Code	Misure esterne mm.			Misure interne mm.			Dimensioni porta mm.		Numero ripiani Number of shelves	Peso Weight	Litri Volume
	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W	Prof/D	Alt/H	Larg/W			
<b>GA/45R</b>	1800	450	450	1600	399	390	1595	450	3	174	249
<b>GA/70R</b>	1800	700	450	1600	649	390	1595	700	3	223	405